# Product Specification

Optic Fiber Adaptor, LC Type, SM

Product Feature:

- Used to mate two connectors together.
- Usually mounted in a distribution panel or PLC splitter
- Push-and-pull structure, convenient for operation
- LC adaptor is available for all standard connector types in both single mode and multimode
- GB/T2828.1-2003 compliance
- GB/T2828.1-2012 compliance

Product Selection

Fiber Core- Joint Form- Type

Fiber Core	Joint Form	Type
Simplex	LC	APC
Duplex		UPC

1.2 Specifications

Parameters	LC/UPC	LC/APC
Working temperature(℃)	-25 - +75	
Insertion Loss(dB)	≤0.2	≤0.2
Durability	≤0.2dB typical change, 1000 matings	

Figure 1

1.2 Siemax product and packing label

Product	Optic Fiber Adaptor
Spec.	LC/APC, Simplex, Single Mode
Value	IL≤0.2dB
Qty.	50Pcs

Figure 2

1.3 Simplex LC type adaptor packing detail

Product Name	Carton Dimension(cm)	Qty.(pcs)
Adaptor, simplex, single mold	26 X 34 X 20	1400

Figure 3

1.3-1 Simplex LC type adaptor Product Packing

Figure 4

1.4 Duplex LC type adaptor packing detail

Product Name	Carton Dimension(cm)	Qty.(pcs)
Adaptor, duplex, single mold	33 X 27 X 20	1000

Figure 5

1.4-1 Duplex LC type adaptor Product Packing

Figure 6